

HB1

whirlwind

STEREO PASSIVE HEADPHONE MONITOR

VOLUME CONTROL

Single knob, stereo pot controls level in the left and right channels simultaneously. Premium quality, sealed, 2 Watt, audio taper pots provide reliability and precise level control.

STEREO/MONO SWITCH

Mono position combines left and right channels into both earpieces.

PHONES OUTPUT

1/4" and 3.5mm jacks are provided, wired in parallel. It is recommended to only use one jack at a time.

POWER AMP LOOP THRU

Parallel wired jacks that can be used for "Daisy chaining" modules.

BELT CLIP

Provides a convenient method of attaching the HB1 for easy access to the controls.

WIRING CONVENTION

Left = Tip = Pin 3 (HB1XL)

Right = Ring = Pin 2 (HB1XL)

Ground = Sleeve = Pin 1 (HB1XL)

HB1XL modules can be connected with standard microphone cables. HB1Q modules can be connected with 1/4" TRS cables.

WARNING - When using headphones with impedances of 50 Ohms or less, do not power the HB1 with an amplifier output rated greater than 50 Watts. Failure to observe this limit will burn out the current limiting resistors inside the unit and void the warranty.

MADE IN USA

99 Ling Road . Rochester, NY 14612
Phone 585 663-8820 . Fax 585 865-8930
Email: sales@whirlwindusa.com
<http://whirlwindusa.com>